

# **TECHNICAL DATA SHEET** WOIL RUBBER GREASE

#### DESCRIPTION

A grease for general applications, has a good oxidation stability, with good resistance to water, heat and corrosion.

### CARACTERISTICS

- Produced from high performance additives and Ca (calcium) soap.
- Contains oxidation preventing additives, therefore it has a longer stocking period.
- Shows high endurance on the bearings that has contact with water and sticks to surface.
- It provides perfect oiling and under heavy-duty conditions, thanks to the additives it contains; High pumping capacity.
- Safely used during every season.

### **APPLICATION**


It is a grease that is made to be used safely on different greasing sports with no special requirements.

#### PERFOMANCE

- DIN: 51502
- DIN: K2K-30
- ISO: 6743
- L-XCCEA4

## **TYPICAL PROPERTIES**

GREEN GREASE				
NLGI No:	0	1	2	3
Color	Green	Green	Green	Green
Soap Туре	Calcium	Calcium	Calcium	Calcium
Penetration (25°C/60 Storke)	355-385	310-340	265-295	220-250
Dropping Point, °C, min.	90	100	100	100
Working Temperature, °C, max.	70	85	85	85





CONTACT US

info@ozersahenerji.com

**9** 

Çerkeşli Köyü Yolu Üzeri GEBKİM Kimyacılar OSB, Atatürk Blv. No:4 Dilovası/Kocaeli, Turkey

