

DESCRIPTION

A high-quality mineral diesel engine oil formulated for trucks and other heavy duty vehicles under various working conditions.

PERFORMANCE

 API: CI-4/SL; ACEA: E7.

APPLICATION

High-performance on turbo diesel engine of heavy duty vehicles that are frequently subject to urban traffic.

CARACTERISTICS

- >> Total engine protection: performance in keeping the engine clean;
- >>> It does not lose its protective properties even under difficult work conditions thanks to the stable durability of the film it forms;
- Drain interval extension: long period between oil change;
- >> Provides efficient protection especially for high-mileage vehicles;
- >> Ensures the trouble-free engine operation in all seasons thanks to its high viscosity index.

TEST	METHOD	UNIT	TYPICAL VALUES
Density @ 15 °C	ASTM D 4052	g/ml	0,88
K. Viscosity @ 40 °C	ASTM D 445	cSt	155,10
K. Viscosity @ 100 °C	ASTM D 446	cSt	19,31
Viscosity İndex	ASTM D 2270		142
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-42

TYPICAL PROPERTIES

ange the first			
10000			

CONTACT US

www.woil.com.tr info@ozersahenerji.com Çerkeşli Köyü Yolu Üzeri GEBKİM Kimyacılar OSB, Atatürk Blv. No:4 Dilovası/Kocaeli, Turkey