



# TECHNICAL DATA SHEET

## GEAR POWER 75W80

### DESCRIPTION

This is a synthetic lubricant based on carefully selected highly refined base oils. Ensures exact friction behavior and provides outstanding ageing resistance. Provides great lubrication security along with ideal wear protection. Enables smooth shifting.

### CARACTERISTICS

- It provides excellent protection against micron-level abrasions on the surface of moving parts.
- Proved high protection against corrosions thanks to its high load carrying capacity.
- By showing excellent performance in all climatic conditions, it facilitates gear change and prevents noise formation.

### APPLICATION

This gear oil provides high performance when used in highway light and heavy duty trucks, busses, and vans.

### PERFOMANCE

- API: GL-4.

### TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density @ 15 °C	ASTM D 4052	g/ml	0,875
K. Viscosity @ 40 °C	ASTM D 445	cSt	80.1
K. Viscosity @ 100 °C	ASTM D 446	cSt	11,75
Viscosity Index	ASTM D 2270		140
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-30



### CONTACT US

www.woil.com.tr  
info@ozersahenerji.com



Çerkeşli Köyü Yolu  
Üzeri GEBKİM Kimyacılar OSB,  
Atatürk Blv. No:4 Dilovası/Kocaeli, Turkey

