



TECHNICAL DATA SHEET

GEAR POWER 80W90

DESCRIPTION

A high-performance automotive transmission oil with an exceptionally high viscosity index. It exhibits excellent fluidity at low temperatures and ensures a long life of the oil and gears.

CARACTERISTICS

- Thanks to its frictional properties it ensures smooth shift performance. It preserves its properties until the next oil change thanks to its high oxidation stability.
- Ensures the extensions of oil life as it has proven resistance to oil degradation.
- Proved high protection against corrosions thanks to its high load carrying capacity.
- Control foam and corrosion occurrence.

APPLICATION

This gear oil provides high performance when used on automotive gear that runs under severe and heavy conditions

PERFORMANCE

- API: GL-4.

TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density @ 15 °C	ASTM D 4052	g/ml	0,89
K. Viscosity @ 40 °C	ASTM D 445	cSt	145,6
K. Viscosity @ 100 °C	ASTM D 446	cSt	min.25
Viscosity Index	ASTM D 2270		min.130
Flash Point	ASTM D 92	°C	min.205
Pour Point	ASTM D 97	°C	max.(-21)



CONTACT US

www.woil.com.tr
info@ozersahenerji.com



Çerkeşli Köyü Yolu
Üzeri GEBKİM Kimyacılar OSB,
Atatürk Blv. No:4 Dilovası/Kocaeli, Turkey

