



TECHNICAL DATA SHEET

PRO POWER 10W40

DESCRIPTION

This is a semi synthetic lubricant based on carefully selected highly refined base oils and advanced additives technologies. Providing outstanding wear and sludge protection, even under the most severe driving conditions.

PERFORMANCE

- API: CI-4

APPLICATION

It is developed to meet the lubrication requirement of the gasoline and light diesel vehicles

CARACTERISTICS

- » Protects the engine from corrosion by providing fast lubrication of the engine parts during the initial operation thanks to its perfect fluidity under cold weather conditions.
- » It minimizes the oil loss thanks to the specially selected synthetic and mineral base oils.
- » The deposit and mud formation are always under control and the engine is kept clean thanks to its active cleaning feature.
- » It perfectly protects the engine under various driving conditions and under every kind of climate condition thanks to its developed high and low temperature properties.

TYPICAL PROPERTIES

10W40 CI-4			
TEST	METHOD	UNIT	TYPICAL VALUES
Density @ 15 °C	ASTM D 4052	g/ml	0,871
K. Viscosity @ 40 °C	ASTM D 445	cSt	109,8
K. Viscosity @ 100 °C	ASTM D 446	cSt	15,23
Viscosity Index	ASTM D 2270		145
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-32



CONTACT US

www.woil.com.tr
info@ozersahenerji.com



Çerkeşli Köyü Yolu
Üzeri GEBKİM Kimyacılar OSB,
Atatürk Blv. No:4 Dilovası/Kocaeli, Turkey

