

DESCRIPTION

Pro Power 5W30 DPF is a full synthetic lubricant that has been developed to meet the requirements for diesel engine vehicles with DPF.

PERFORMANCE

- API: SN/CF,
- ACEA: C4,
- MB: 229.51.

APPLICATION

This type of pro power 5W30 is suitable for all LPG, gasoline, and diesel engines. Recommended for every season and any severe driving conditions.

CARACTERISTICS

- >> Total engine protection and high performance in keeping the engine clean;
- >> Superior fuel economy;
- >>> Cold start and excellent fluidity at low temperature;
- >> Provides high engine performance by reducing the friction;
- Provide protection against power lost and ensure continuity of engine functioning;
- >> Top level residue and soot control.

TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density @ 15 °C	ASTM D 4052	g/ml	0,86
K. Viscosity @ 40 °C	ASTM D 445	cSt	65,37
K. Viscosity @ 100 °C	ASTM D 446	cSt	11,18
Viscosity İndex	ASTM D 2270		165
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-40



CONTACT US

www.woil.com.tr info@ozersahenerji.com Çerkeşli Köyü Yolu Üzeri GEBKİM Kimyacılar OSB, Atatürk Blv. No:4 Dil<u>ovası/Kocaeli, Turkey</u>

